

In the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims

1. (Currently Amended): An AFE (analog front end) device of a LCD controller with adjustable bandwidth filtering functions, the AFE device comprising an input buffer for buffering an analog signal and an ADC (analog-to-digital converter) for converting the analog signal into a digital signal, the ADC having the adjustable bandwidth filtering functions and comprising:

a capacitor for sampling and holding the analog signal; and

a switch module serially ~~connected~~ coupled to the capacitor, the switch module comprising a plurality of transistor switches ~~connected~~ coupled in parallel, wherein the switch module ~~selects, according to a selection code,~~ at least one of the transistor switches is selected as an equivalent resistor according to a selection code, so as to constitute a filter circuit together with the capacitor;

wherein the selection code is corresponding to a designate filtering bandwidth of the AFE device.

2. (Previously Presented): The AFE device according to claim 1, wherein the selection code is a one-of-N code, and one of the transistor switches is selected as the equivalent resistor according to the one-of-N code.

3. (Previously Presented): The AFE device according to claim 1, wherein the selection code is a thermometer code, and one of the transistor switches is selected, or multiple ones of the transistor switches connected in parallel are selected as the equivalent resistor according to the thermometer code.

4. (Previously Presented): The AFE device according to claim 1, further comprising a switch serially connected to the capacitor.

5. (Currently Amended): An AFE (analog front end) device of a LCD controller with adjustable bandwidth filtering functions, the AFE device comprising an input buffer for buffering an analog signal and an ADC (analog-to-digital converter) for converting the analog signal into a digital signal, the input buffer having the adjustable bandwidth filtering functions and comprising:

[[A]] a current source; and

[[A]] a transistor module serially ~~connected~~ coupled to the current source to form a source follower, the transistor module comprising a plurality of transistors ~~connected~~ coupled in parallel, wherein ~~the transistor module selects, according to a selection code, at least one of the transistors is to be serially connected~~ coupled to the current source according to a selection code, so as to form a filter circuit;

wherein the selection code is corresponding to a designate filtering bandwidth of the AFE device.

6. (Previously Presented): The AFE device according to claim 5, wherein the selection code is a one-of-N code, and one of the transistors is selected to be serially connected to the current source according to the one-of-N code.

7. (Previously Presented): The AFE device according to claim 5, wherein the selection code is a thermometer code, and one of the transistors is selected or multiple ones of the transistors are selected to be connected in parallel with each other or one another and then to be serially connected to the current source according to the thermometer code.

8. (Previously Presented): The AFE device according to claim 5, wherein the transistor module has an input terminal serially connected to an impedance.

9. (Previously Presented): The AFE device according to claim 8, wherein the impedance is equivalent to and implemented by a transistor switch.

10. (Currently Amended): An AFE (analog front end) device of a LCD controller with adjustable bandwidth filtering functions, the AFE device comprising an input buffer for buffering an analog signal and an ADC (analog-to-digital converter) for converting the analog signal into a digital signal, the input buffer having the adjustable bandwidth filtering functions and comprising:

a transistor; and

a current source module serially ~~connected~~ coupled to the transistor to form a source follower, the current source module comprising a plurality of current sources ~~connected~~ coupled

in parallel to each other or one another, wherein ~~the current source module selects, according to a selection code,~~ at least one of the current sources ~~to be~~ is serially connected coupled to the transistor according to a selection code, so as to form a filter circuit;

wherein the selection code is corresponding to a designate filtering bandwidth of the AFE device.

11. (Previously Presented): The AFE device according to claim 10, wherein the selection code is a one-of-N code, and one of the current sources is selected to be serially connected to the transistor according to the one-of-N code.

12. (Previously Presented): The AFE device according to claim 10, wherein the selection code is a thermometer code, and one of the current sources is selected or multiple ones of the current sources are selected to be connected in parallel with each other or one another and then to be serially connected to the transistor according to the thermometer code.

13. (Previously Presented): The AFE device according to claim 10, wherein the transistor has an input terminal serially connected to an impedance.

14. (Previously Presented): The AFE device according to claim 13, wherein the impedance is equivalent to and implemented by a transistor switch.

15-27. (Canceled)

28. (New): The AFE device according to claim 1, wherein at least two transistor switches have different width-to-length ratios.

29. (New): The AFE device according to claim 1, wherein the selection code is generated in response to the designate filtering bandwidth of the AFE device.

30. (New): The AFE device according to claim 5, wherein at least two transistors have different sizes.

31. (New): The AFE device according to claim 5, wherein the selection code is generated in response to the designate filtering bandwidth of the AFE device.

32. (New): The AFE device according to claim 10, wherein the selection code is generated in response to the designate filtering bandwidth of the AFE device.